



FXMQ-P7-High static pressure

INDOOR UNIT				FXMQ20P7	FXMQ25P7	FXMQ32P7	FXMQ40P7	FXMQ50P7	FXMQ63P7	FXMQ80P7	FXMQ100P7	FXMQ125P7
Cooling capacity	Nom.		kW	2.2	2.8	3.6	4.5	5.6	7.1	9.0	11.2	14.0
Heating capacity	Nom.		kW	2.5	3.2	4.0	5.0	6.3	8.0	10.0	12.5	16.0
Power input - 50Hz	Cooling	Nom.	kW	0.049		0.053	0.151	0.110	0.120	0.171	0.176	0.241
	Heating	Nom.	kW	0.037		0.041	0.139	0.098	0.108	0.159	0.164	0.229
Casing	Colour		Unpainted Galvanised steel plate									
	Material											
Dimensions	Unit	HeightxWidthxDepth	mm	300x550x700			300x700x700	300x1,000x700			300x1,400x700	
Required ceiling void >			mm	350								
Weight	Unit		kg	23			26	35			46	
Decoration panel	Model			BYBS32DJW1			BYBS45DJW1	BYBS71DJW1			BYBS125DJW1	
	Colour			White (10Y9/0.5)								
	Dimensions	HeightxWidthxDepth	mm	55x650x500			55x800x500	55x1,100x500			55x1,500x500	
	Weight		kg	3.0			3.5	4.5			6.5	
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low	m³/min	9/7.8/6.5		9.5/8.3/7	16/13.5/11	18/16.5/15	19.5/17.8/16	25/22.5/20	32/27.5/23	39/33.5/28
	Heating	High/Nom./Low	m³/min	9.0/7.8/6.5		9.5/8.3/7	16/13.5/11	18/16.5/15	19.5/17.8/16	25/22.5/20	32/27.5/23	39/33.5/28
Fan-External static pressure - 50Hz	High/Nom.		Pa	100/50			160/100	200/100				
Sound power level	Cooling	High/Nom.	dBA	56/-		57/-	65/-	61/-	64/-	67/-	65/-	70/-
	Heating	High/Nom./Low	dBA	33/31/29		34/32/30	39/37/35	41/39/37	42/40/38	43/41/39		44/42/40
Sound pressure level	Cooling	High/Nom./Low	dBA	33/31/29		34/32/30	39/37/35	41/39/37	42/40/38	43/41/39		44/42/40
	Heating	High/Nom./Low	dBA	33/31/29		34/32/30	39/37/35	41/39/37	42/40/38	43/41/39		44/42/40
Refrigerant	Type			R-410A								
Piping connections	Liquid/OD/Gas/OD/Drain		mm	6.35/12.7/VP25 (I.D. 25/O.D. 32)					9.52/15.9/VP25 (I.D. 25/O.D. 32)			
Air filter	Type			Resin net with mold resistance								
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220								
Current - 50Hz	Maximum fuse amps (MFA)		A	16								



FXMQ-MA



BRC1E52A/B

BRC4C65

- › Up to 270Pa external static pressure allows extensive ductwork runs and flexible application: ideal for use in large areas
- › Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible
- › Up to 31.5kW in heating mode



INDOOR UNIT			FXMQ200MA		FXMQ250MA	
Cooling capacity	Nom.	kW	22.4		28.0	
Heating capacity	Nom.	kW	25.0		31.5	
Power input - 50Hz	Cooling	Nom.	1.294		1.465	
	Heating	Nom.	1.294		1.465	
Dimensions	Unit	HeightxWidthxDepth	mm		470x1,380x1,100	
Weight	Unit		kg		137	
Fan-Air flow rate - 50Hz	Cooling	High/Low	m ³ /min		58/50	
Fan-External static pressure - 50Hz	High/Nom.		Pa		221/132	
Sound power level	Cooling	Nom.	dBA		-	
Sound pressure level	Cooling	High/Low	dBA		48/45	
Refrigerant	Type				R-410A	
Piping connections	Liquid/OD/Gas/OD/Drain		mm		9.52/19.1/PS1B	
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50/60/220-240/220	
Current - 50Hz	Maximum fuse amps (MFA)		A		15	